



DKM GREASE

LITHIUM MP

DKM Lithium MP Grease is automotive and industrial grease made from a combination of lube base oil and high quality lithium soap and also equipped with functional additives that protect against oxidation and resistance to rust (Corrosion).

DKM Lithium MP Grease is suitable for use in both automotive and industrial such as: heavy equipment, wheel bearing, roller bearing, etc.

DKM Lithium MP Grease adalah gemuk otomotif dan industri yang terbuat dari kombinasi bahan dasar minyak pelumas dan jenis lithium soap yang berkualitas tinggi serta dilengkapi dengan aditif fungsional yang melindungi dari oksidasi dan daya tahan terhadap karat (Korosi).

DKM Lithium MP Grease sangat sesuai digunakan pada otomotif dan industri seperti: alat-alat berat, bantalan roda, bantalan rol, dsb.

BENEFITS | KEUNTUNGAN

DKM Lithium MP Grease provides the following benefits :

- Prolong wheel bearing life
- Resistant to heavy load
- Excellent water washing resistance
- Extra strong adhesive
- Prevent friction, rust, and oxidation
- Highly stable under high operating temperature

DKM Lithium MP Grease memberikan manfaat sebagai berikut :

- Memperpanjang kegunaan bantalan roda
- Tahan terhadap beban berat
- Tahan terhadap sapuan air
- Berdaya lekat ekstra kuat
- Mencegah terjadinya friksi (pergesekan), karat, dan oksidasi
- Sangat stabil saat beroperasi pada suhu tinggi

TYPICAL CHARACTER

| Characteristics | Test Method | Specification |
|---|-------------|--|
| Colour / Warna | Visual | Yellow Transparent / Kuning Transparan |
| Texture / Tekstur | Visual | Smooth and Tacky / Lembut dan Lengket |
| Type Of Thickener / Jenis Pengental | - | Lithium |
| NLGI Grade | NLGI | 3 |
| Worked Penetration @ 25°C / Kinerja Penetrasi pada 25°C | ASTM D 217 | 240 - 290 |
| Dropping Point, °C / Titik Jatuh, °C | ASTM D 566 | 190 min. |
| Wear Scar Dia. (Four Ball), mm | ASTM D 2266 | 0.26 |
| Resistance to Water Washout (38°C, 1hr) / Ketahanan Terhadap Sapuan Air (38°C, 1hr) | ASTM D 1264 | 5 max |